

TIMBERLINE FOLDING DOORS

INSTALLATION INSTRUCTIONS

Dear Customer,

We are pleased you have chosen a quality Timberline Folding Door. When installed correctly, it should give you lasting, trouble free use.

1. CONTENTS

Open the box, locate the bag of screws and small parts and identify each.

Ref	Size & Type	Colour	Item	Quantity	Refer below Paragraph
1	25mm x 8g Pan head	Sliver	Track Screws	Approx. 3/metre	2.2
2	25mm x 8g Pan head	Red	Hold back screw in track	1 or 2	2.2 & 2.6
3	25mm x 8g Pan head	Yellow	Centre stop in track for pairs	Optional, 1	2.7
4	40mm x 8g c/sunk and covercaps		Track mould screws	Approx. 4/metre	2.8
5	25mm x 8g c/sunk and covercaps		Backflap screws	6 - 10	2.3
6	25mm x 6g c/sunk	Matching	To fix receiving channel	6 - 10	2.4
7	Handles	Matching	Complete with lever	1 pair/door	2.5
8	2 screws & washer	Matching	To join handles together	2 sets/door	2.5
9	Cylinder & 30mm screw	Chrome	Lock cylinder & key	Optional, 1	2.5
10	80mm long	Silver	Joining pins (already in track)	2 / join	3.1
11	40mm long	Silver	Keeper	1	2.4
12	10mm x 8g c/sunk	Silver	Keeper screws	2	2.4
13	40mm long	Black	Keeper packer	1	2.4

2. PRE-ASSEMBLED DOORS (For larger doors, supplied in segments, refer to paragraph 3)

2.1 Track orientation

Look at the top of the track and read the note to ensure the track is the correct way around. Offer the track up and mark and drill all holes for the track screws. Don't screw in yet. Bunch the door up and feed the track over the trolleys. Take care that the track is the right way round.

2.2 Fixing the track and door to the door frame head

Offer the track to the door head and screw in place (#1 & 2). ENSURE THE RED HOLD BACK SCREW GOES IN THE CORRECT HOLE, marked on the outside with the red dot. If your door is a bi-parting pair there will be a centre stop screw (Yellow). See paragraph 2.7 below. **DO NOT PUT THIS IN YET.**

Note: If your track is supplied in more than one length, read paragraph 3.1

2.3 Attaching the door to the door frame

Push the door back into the fully open position. Let it hang naturally. Mark on the doorframe at the top and bottom to note where the backflap hangs plumb vertical against the door frame. Close the door halfway. Fix the backflap to the mark on the door frame, starting at the bottom, using screws (#5) and cover caps.

2.4 Fitting the receiving channel and keeper

TAKE CARE: The channel must have the Lotus sticker at the TOP and must butt up hard to the track. Put the top screw (#6) in first, loosely, and by closing the door into the channel, note the natural hanging position of the channel and then fix the bottom screw only. Align the keeper (#11) with the latch and screw in place with the 2 keeper screws (#12). Care: Ensure keeper knob is to top. Test the alignment to see the door shuts easily and naturally. If the door doesn't easily latch onto the keeper it may be because the door frame is bowed. A packer is included to go behind the keeper if necessary (#13). Now fix the remaining channel screws.

2.5 Fitting the handles

Handles have been supplied loose to avoid the risk of transit damage. Position the handles to either side of the latch with the raised part to the rear. Ensure the lever is at the top of the handle and hanging down naturally to engage it in the square slot in the latch mechanism. Fix with the screw, washer and blind screw (#3) through the top and bottom holes in the handles and tighten. If supplied with a cylinder lock, position this in the latch so the cam turns towards the front of the door, secure with screw (#9) from the front of the latch.

2.6 Adjusting the "Hold Open" Screw

Partly open the door and unscrew the RED holdback screw a few turns until it engages with the leaf spring on top of the roller carriage on the end-post to hold the door in the open position without requiring a lot of effort to close it again. Carefully adjust +/- 1/4 turn for correct operation. A slight downwards pressure on the handle will assist with closing the door from its held-back position.

2.7 Bi-parting Pairs

Proceed as above for each side. There is an additional YELLOW screw (#3) which should be fixed in the track in centre to prevent either half door stretching beyond half way, refer yellow dot on track. Screw in only half way do this once all other installation work is completed.

2.8 Track Moulds

Fix the trackmoulds either side of the track using screws (#4) and cover caps. Trackmoulds will be a little over length to give you the opportunity of cutting to length and ensuring a neat fit regardless of the type of door frame.

3. DOORS NOT PRE-ASSEMBLED

Due to the size of door Timberline door, it is packed in more than one box. These are numbered on the outside of each box and also on the bottom of the door segments themselves as follows: (Diagram below is looking down from above the door). Refer to the installation instructions in Paragraph 2 in conjunction with the additional notes below.

3.1 Multiple Tracks

Put the track up using the joining pins (#10) to align junctions and follow the sequence AA etc. Leave one end piece off to enable panels to be fed on to tile track. Knock the joining pins into the last piece of track, offer up to slide the pins across the join before screwing to the head. Ensure the track is exactly horizontal (otherwise, for bi-parting pairs of doors, there could be an uneven gap between end-posts when closed).

3.2 Joining Multiple door segments

Feed the door segments on to the track in the sequence shown above. Check that the segments are in the correct sequence. Ensure the first segment is fed on with the backflap with pre-drilled holes towards the jamb. Ensure the hinge-mould on one section is opposite a grooved panel in its adjacent section. Squeeze some wood-glue into the groove at the top, bottom and middle of the panel for about 50mm (there's no need to glue the whole length of the groove). Firmly tap the hinges in to join the whole door together. Ensure hinges are fully-tapped in all the way down their length.

4. CLEANING

Use warm soapy water or on real veneers only, furniture polish.



**FOLDING
DOORS**

Ph: (07) 3266 4807
Fax: (07) 3314 7722
Email: sales@foldingdoors.com.au
Web: www.foldingdoors.com.au